



Blue Monster® PTFE Thread Seal Tape - Professional Grade

Rugged, general purpose tape in a monstrous 1429" roll!
Ideal for hundreds of applications.

Blue Monster is a higher-quality PTFE sealing tape that is easier to apply. Blue Monster has not been stretched during the manufacturing process, so it is thicker and creates a more effective seal with less tape, and no need for pipe dope. Use Blue Monster on threads made from galvanized steel, iron, brass, copper, aluminum, stainless steel, polyethylene, polypropylene, PVC, CPVC, ABS, fiberglass and more.



Cat #	Description	Std. Pkg.	Master Pkg.	Wgt./Pkg.
70885	1/2" x 1429" Rolls	45	270	5.5 lbs.
70886	3/4" x 1429" Rolls	27	162	5.0 lbs.
70887	1" x 1429" Rolls	27	162	5.75 lbs.

Specifications: Seals fittings at pressures up to 10,000 PSI. Temperature range -450°F to +500°F (-268°C to +260°C).

- Seals threads effectively in more applications.
- Acts as a thread lubricant and anti-seize.
- Effective across a broad range of temperatures and pressures.
- Easier to use - no waste! Will not harden or crack.



Blue Monster Industrial Grade Thread Sealant

BLUE MONSTER Industrial Grade Pipe Thread Compound is a slow-drying, soft-setting, non-hardening pipe thread compound. Specially formulated with superb "sticking" characteristics, BLUE MONSTER applies evenly and quickly to threads. Recommended for on-site or assembly line work, BLUE MONSTER is lead-free, non-toxic and will not harden or separate in the can.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76009	1/4 pint / 4 fl. oz. / 118 ml	24	15 lbs.
76011	1/2 pint / 8 fl. oz. / 237 ml	24	23 lbs.
76015	1 pint / 16 fl. oz. / 473 ml	12	22 lbs.
76019	1 quart / 32 fl. oz. / .95 liter	12	42 lbs.

Meets Mil. Spec. TT-S-1732
Brushable from -50°F (-45°C) to +400°F (204°C)
Pressure ratings: Gases up to 3,000 PSI (211 kg/cm²)
Liquids up to 6,000 PSI (422 kg/cm²)
Not recommended for use on oxygen systems. Use Clean-Fit 3-wrap Oxygen PTFE Tape.



pw/dww/sw
Standard 14
Standard 61

Blue Monster Industrial Grade Thread Sealant with PTFE

Formulated for extra lubrication on metal pipe threads, BLUE MONSTER Industrial Grade Thread Sealant with PTFE is a slow-drying, soft-setting, non-hardening pipe thread compound. BLUE MONSTER has a high bulk density, which means there are more solids in the formulation. Recommended for on-site or assembly line work. It is lead-free, non-toxic and will not harden or separate in the can.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76001	1/4 pint / 4 fl. oz. / 118 ml	24	15 lbs.
76003	1/2 pint / 8 fl. oz. / 237 ml	24	23 lbs.
76005	1 pint / 16 fl. oz. / 473 ml	12	22 lbs.
76017	1 quart / 32 fl. oz. / .95 liter	12	42 lbs.

Meets Mil. Spec. TT-S-1732
Brushable from -50°F (-45°C) to +400°F (204°C)
Pressure ratings: Gases up to 3,000 PSI (211 kg/cm²)
Liquids up to 10,000 PSI (703.1 kg/cm²)
Not recommended for use on oxygen systems. Use Clean-Fit 3-wrap Oxygen PTFE Tape.



ANSI
LC7-2009



pw/dww/sw
Standard 14
Standard 61

Blue Monster Stay-Soft Thread Sealant with PTFE

Blue Monster Stay-Soft PTFE enriched pipe thread compound does not harden and allows for pre-fab application to threads weeks before system assembly and pressurization. Stay-Soft is non-seizing and allows for easy disassembly of any threaded connection years after assembly.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76023	1/4 pint / 4 fl. oz. / 118 ml	24	18 lbs (8.2 kg)
76025	1/2 pint / 8 fl. oz. / 237 ml	24	26 lbs (11.8 kg)
76027	1 pint / 16 fl. oz. / 473 ml	12	25 lbs (11.3 kg)
76029	1 quart / 32 fl. oz. / .95 liter	12	50 lbs (22.7 kg)

Formulated for the fire protection industry.

Approved for use on all metal threaded connections, FlowGuard Gold®, Blazemaster®, and Corzan® pipe and fittings.



Brushable from -15°F (-20°C) to +400°F (204°C)
Pressure ratings: Gases up to 5,000 PSI (351.5 kg/cm²)
Liquids up to 10,000 PSI (703.1 kg/cm²)

